

### OPERATING MANUAL



## ⚠ WARNING



### FOR YOUR SAFETY AND TO PREVENT INJURY:

- Read, understand & follow these instructions and warnings before use.
- It is the responsibility of the owner to make sure all personnel read this manual prior to using the device. It is also the responsibility of the device owner to keep this manual intact and in a convenient location for all to see and read. If the manual or product labels are lost or not legible, contact Mac Tools for replacements. If the operator is not fluent in English, the product and safety instructions shall be read and discussed with the operator in the operator's native language by the purchaser/owner or his designee, making sure that the operator comprehends its contents.
- Always wear safety goggles (including users & bystanders).
- Never use the suction gun with gasoline or diesel fuel.
- Do not allow hose to kink. Do not bend the hose in a tight radius.
- Do not eject any retained fluid from the Suction Gun at a rapid rate or with a larger force, as this may cause the fluid to splatter and damage the operator or surrounding item.
- This product may contain one or more chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. *Wash hands thoroughly after handling.*
- Failure to heed these warnings may result in serious or fatal personal injury and/or property damage.

## FEATURES AND FUNCTIONS

- 16 oz. Capacity
- Heavy-Duty 1.7mm thick seamless barrel
- Barrel features special textured finish
- Heavy-Duty "T" handle with finger grooves

## PROPER SUCTION GUN USE

This Suction Gun should only be used for its designed purpose and according to the instructions in this manual.

## GENERAL CAUTIONARY NOTES

Do not allow bystanders, children or other on-lookers in the work area as they can cause distractions, which may lead to mistakes and accidents.

Carefully inspect the equipment for damaged, loose or missing parts. If the unit is worn or damaged, do not use it.

## ASSEMBLY INSTRUCTIONS

1. Attach the 12" clear plastic tube to the fitting at the end of the suction gun.

**Note:** Oil can be used to lubricate the fitting if it is too tight.

## OPERATING INSTRUCTIONS

1. Pull back the "T" shaped handle to operate.

**Note:** Place a finger over the end of the tube to stop any fluids from leaking or dripping after removal. Fluids that are difficult to extract when cold can be easier to extract when warmed up by operating the vehicle.

2. To force out the fluid from the suction gun, push the "T" shaped handle into the barrel.

**Note:** Whenever adding fluids, make sure the gun is cleaned before filling with clean fluid.